



8355 CrownShield® Pigmented Epoxy Receiving Coat for Color Flake

TECHNICAL DATA SHEET Product Number: 8355

High Build Pigmented Epoxy Binder to Receive Broadcasted Vinyl Color Chips

DESCRIPTION

8355 CrownShield is a 2 component, high build, high pigmented load epoxy binder that is specially designed to receive CrownFlake System vinyl chips 1/8 inch and 1/4-inch flakes. It is self-priming and it is formulated as a moisture tolerant epoxy binder and bonds tenaciously dry or damp concrete. It can be applied directly to “saturated surface dry” (SSD) concrete slabs on grade (with no standing water). The high pigment load design means that it easily hides concrete between 160 to 200 square feet (14.9 to 18.9 sq. m) in a single coat application. It has ample working time to cut-ins, place, and broadcast the vinyl chips. CrownShield No. 8355 Accelerator (6 wt. oz. per 2 gals) is available when rapid cure is required. It is VOC Compliant in all states and provinces in North America.

TYPICAL USE

- **Animal Care and Housing Floors**
- **Automotive Show Room and Repair Floors**
- **Commercial Bakeries and Kitchens Floors**
- **Food, Beverage and Spirits Processing**

- **Do not use as a primer when concrete slab exceeds 3 lbs. or 80% RH.**

COLORS

Available in factory pigmenting light gray, medium gray, dark gray, black, light tan, tan, and sand beige.