COATING APPLICATION TOOLS

MIDWEST RAKE

Bon Wizard™ Squeegee

CAM

POWERBRACE

MIDWEST RAKE S550

MIDWEST RAKE S550 PROFESSIONAL™ EASYSQUEEGEE™

CLEANABLE & REUSABLE

PATENT PENDING, US

PRECISION APPLICATION SQUEEGEE SYSTEM

INTELLIGENT BLADE IDENTIFICATION

All blades inscribed with WFT and WFSR information.

SELF-LEVELING BLADES

Accurate and predictable Wet Film Thickness every time.

SELF-LOCATING BLADES

Designed to provide industry leading accuracy.

PROTECTED THREADS AND FASTENERS

Eliminates material contact with threads.

THUMB SCREWS REPLACE NUTS

Features Cured Coatings Release (CCR™) Technology for cleanability.

CURED COATINGS RELEASE™ TECHNOLOGY

Ensures the frame is reusable regardless of the material used.

BLADE STIFF	BLADE WIDTH 9"	13"	19"	27"	SAMPLE PROJECT APPLICATIONS
FLAT FLEXIBLE	•			•	Do you prefer a thinner more flexible blade for your coatings application? Or do you prefer pulling vs. pushing?
FLAT STIFF		•	•		Do you have a large area to coat with a thin film clear epoxy or urethane topcoat?
5-7 WFT MILS WITH 2.5# GAL/FT² SOL.		•	•		Tasked with pulling a rapid curing polyaspartic urethane clear-coat over a random flake floor?
8-12 WFT MILS WITH 1.5# GAL/FT² SOL.		•	•		Need to get 2500 gallons or 1500's solids epoxy down at 10 Mils (160 ft²/ GAL) with an irregular/uneven/ work-crew?
15-20 WFT MILS WITH 1.5# GAL/FT² SOL.		•	•		Applying a decorative 100% solids metallic epoxy at 120 ft² / GAL?
25-30 WFT MILS WITH 1.5# GAL/FT² SOL.		•	•		Looking to squeegee apply 30 Mils (80 ft²/ GAL) of silicone roof coating?
40-45 WFT MILS WITH .5# GAL/FT² SOL.		•	•		Are you applying 40 Mils of polyurethane deck coating to a large parking structure?
50-60 WFT MILS WITH .5# GAL/FT² SOL.		•	•		Need to apply 60+ Mils of an epoxy waterproofing to a bridge deck?

MIDWEST RAKE S550 EASYSQUEEGEE

MIDWEST RAKE S550 EASYSQUEEGEE FLAT STIFF PLAT ET RAIDE PLANA Y RÍGIDA

MIDWEST RAKE S550 EASYSQUEEGEE 8-12 WFT MILS

MIDWEST RAKE S550 EASYSQUEEGEE 15-20 WFT MILS

MIDWEST RAKE S550 EASYSQUEEGEE FLAT FLEXIBLE with EXTENDED WING PLATE ET FLEXIBLE avec AILE ALLONGÉE FLEXIBLE Y PLANO con ALA AMPLIADO

DISPLAY

24" FLOOR COATER REFILL Nyfoam®