



8101 CrownSeal™ Acrylic-WB Low Viscosity Grout & Sealer

TECHNICAL DATA SHEET Product Number: 8101

Water Base, Low Viscosity, Acrylic Grout and Sealer Concrete, Masonry & Brick

DESCRIPTION

8101 CrownSeal is a single component, waterborne, ultraviolet stable, high-performance, fast-drying acrylic emulsion. It is used as a vinyl chip as a clear grout coat, and it is used as a Concrete, Cementitious Overlays, Masonry and Porous Bricks and Pavers sealer. As a grout coat for CrownFlake vinyl chips it should be placed at 200 sq. ft. (18.6 sq. m.) per gallon. As a sealer place of clean, sound, and durable Concrete, Cementitious Overlays, and Masonry at 300 to 350 sq. ft. (27.9 to 32.5 sq. m.) per gallon. Porous Bricks and Porous Pavers the sealer demand will vary depending on their porosity. It is VOC Compliant in all states and provinces in North America.

TYPICAL USE

- Grout Coat for Color Flake
- Sealer for Concrete, Cementitious Overlayment, and Masonry
- Sealer for Porous Bricks or Porous Pavers

COVERAGE RATE

- Color Flake Grout at 200 sq. ft. (18.6 sq. m.) per gallon.
- Sealer on Concrete, Cementitious Overlayment, and Masonry at 300 to 350 sq. ft. (27.9 to 32.5 sq. m.) per